



The LCD control panel is preset at the factory on a time basis .

The cylinders show filter time life for each filter, the membrane having the highest number

Unfortunately, the preset cannot be altered, they set them at 3 months

This time period is way lower than the filters require changing ( we would expect 12 months for this )

When the cylinder goes down to zero, eg all the bars disappear in the cylinder a silent alarm will show

Thankfully, you can manually re set the cylinders to show all bars, and they will count down again

Press the top button (select) on the control panel, the first filter cylinder will flash.

Below are the instructions to manually re set if required

Key function description

The board is equipped with three key switches: selection key (TOP), confirm key(MIDDLE) and strong punch key.

Press the TOP button to enter the setting mode, the first filter will flash

Press the MIDDLE button the bars should fill the cylinder

Press the top button and the first filter will flash, press gain and the 2<sup>nd</sup> filter will flash

Press middle button to re set

Repeat with remaining filters

Press the selection key, if you don't press the OK (Affirm) key or the selection key within 5 seconds, you will automatically exit the setting mode.

The LCD control panel is preset at the factory on a time basis .

The cylinders show filter time life for each filter, the membrane having the highest number

Unfortunately, the preset cannot be altered, they set them at 3 months

This time period is way lower than the filters require changing ( we would expect 12 months for this )

When the cylinder goes down to zero, eg all the bars disappear in the cylinder a silent alarm will show

Thankfully, you can manually re set the cylinders to show all bars, and they will count down again

Press the top button (select) on the control panel, the first filter cylinder will flash.

Below are the instructions to manually re set if required

Key function description

The board is equipped with three key switches: selection key (TOP), confirm key(MIDDLE) and strong punch key.

Press the TOP button to enter the setting mode, the first filter will flash

Press the MIDDLE button the bars should fill the cylinder

Press the top button and the first filter will flash, press gain and the 2<sup>nd</sup> filter will flash

Press middle button to re set

Repeat with remaining filters

Press the selection key, if you don't press the OK (Affirm) key or the selection key within 5 seconds, you will automatically exit the setting mode.

